

1. SPECIFICATIONS

AMF-O60F42-1FWH


01	Electret's Type	Foil type
02	Sensitivity	-42±3dB (0dB=1V/Pa,1KHz)
03	Standard Operation Voltage	2.0 V
04	Output Impedance	2.2 KΩ
05	Directivity	Omni directional
06	Frequency Range	20 – 16 K Hz
07	Max. Operation Voltage	10V
08	Current Consumption	Max.0.5mA
09	Sensitivity Reduction	Within -3dB 0dB=1V/Pa,1KHz Vs=2.0to 1.5V
10	S/N Ratio	≥ 60dB
11	Sound Pressure Level	110 dB

REV NO.

REVISION NOTE

APPROVAL

DATE



Wire : UL1571,AWG30#
 Holder : DD-EQ-JTC75-03
 Connector:Equivalent to Molex 51021-0200

RoHS

TITLE: <i>MICROPHONE</i>		DRAWN: <i>Zack</i> 2015/10/14	SCALE: 5:1	SHEET: 1 of 1
PART NO. <i>AMF-060F42-1FWH</i>		DESIGNED: R & D OF AAT	UNITS: mm	
DWG NO. <i>F6027AL-SYGP-D63-M 11297</i>		CHECKED:	TOLERANCE ± 0.3	
		APPROVAL:	UNLESS OTHERWISE SPECIFIED: ONE PLACE DECIMAL ± *** TWO PLACE DECIMAL ± *** THREE PLACE DECIMAL ± ***	
REV <i>2</i>		MATERIAL: AL		



ADVANCED ACOUSTIC TECHNOLOGY CORPORATION

For more information, please contact AATC.

AATC