
1. SPECIFICATION

AKB-64220420-PPC-1C

ITEM		SPECIFICATIONS	
01	**Type**	Dynamic Speaker	
02	**Dimension**	External diameter 63.5 x 22.4 mm	
03	**Rated Input Power**	2.0 W	
04	**Max. Input Power**	2.5 W for 1 minute	
05	**Impedance**	4Ω ± 15% at 1 KHz 1V	
06	**Resonance Frequency (Fo)**	800 Hz ± 20% at Fo, 1V	
07	**Sound pressure level**	105dB(2.0W/0.1M) ± 3 dB	at AVE 0.8, 1.0, 1.2, 1.5 KHz.
08	**Frequency Range**	Fo – 3K Hz	
09	**Total Harmonics Distortion**	Max 10 % at 1 KHz, 1W	

AAC

REV NO.	REVISION NOTE	APPROVAL	DATE



WIRE : UL 1571,AWG28#

CONNECTOR :Equivalent to JST PHR−2

RoHS

TITLE: DYNAMIC SPEAKER	DRAWN: Zack 2017/05/10	SCALE: 1:1	SHEET: 1 : 1
PART NO. AKB−64220420−PPC−1C	DESIGNED: R & D OF AAT	UNITS: mm	
DWG NO. CXS2040180LP500−R04W2.0−D	CHECKED:	TOLERANCE ± 0.5	
3 REV	APPROVAL:	UNLESS OTHERWISE SPECIFIED: ONE PLACE DECIMAL ± *** TWO PLACE DECIMAL ± *** THREE PLACE DECIMAL ± ***	
	MATERIAL: ABS		

ADVANCED ACOUSTIC TECHNOLOGY CORPORATION

For more information, please contact AATC.

AATC